


Model No.	TD-2003
	
RH Control Range	≤ 20% RH
Fast Recovery Time	Recovers to ≤ 20% RH within 30 minutes after accessing door for 30 seconds or less.
External Dimension	W1200 x H1950 x D714mm
Internal Dimension	W1100 x H1700 x D610mm
Capacity	1329 Liter
Cabinets	Anti-static Paint on Body and Shelves Antic-Static Glass (Thickness:3mm), Anti-static Caster / Stands, 1 M Ω Ground Wire
Cabinet Material	Made by SECC/ Thickness:1mm
Cabinet Color	Grey
Anti Static Painting	Surface Resistivity ≤100kΩ
Shelves	5pcs of metal shelves with anti-static painting (Height adjustable)
Loading Capacity of Shelf	100kg
Doors	6 doors with locks
Core Units	In the event of a power failure, dehumidification is maintained with doors closed
Voltage	220V
Hygrometer	3rd Party monitor system, TESTO digital thermal hygrometer
Hygrometer measuring range & accuracy	0-95%RH ±3%RH 0-50°C±0.5°C
Indicator	Have power indicator in the cabinet and operating indicator on core units
Ave Power Consumption	72w
Dual RH Sensor Design	Built-in independent sensors in the drying system and hygrometer provides RH monitoring independent of each other
Brand	Eureka
Country of Manufacture	Taiwan

For more information, contact us at [enquiry@drycabinets.com.sg](mailto:enquiry@drycabinets.com.sg)  
or simply give us a call at 67491812