


Model No.	TUS-1003
	
RH Control Range	10%-50% RH
Fast Recovery Time	Recovers to $\leq 20\%$ RH within 2 hours after accessing door for 30 seconds or less.
External Dimension	W600 x H1950 x D714mm
Internal Dimension	W560 x H1700 x D610mm
Capacity	665 Liters
Cabinets	Anti-static Paint on Body and Shelves Antic-Static Glass (Thickness:3mm), Anti-static Caster / Stands, 1 M Ω Ground Wire
Cabinet Material	Made by SECC/ Thickness:1mm
Cabinet Color	Grey
Anti Static Painting	Surface Resistivity $\leq 100k\Omega$
Shelves	5 pcs of metal shelves with anti-static painting (Height adjustable)
Loading Capacity of Shelf	100kg
Doors	3 doors with locks
Core Units	In the event of a power failure, dehumidification is maintained with doors closed
Voltage	220V
Hygrometer	3rd Party monitor system, TESTO digital thermal hygrometer
Hygrometer measuring range & accuracy	0-95%RH $\pm 3\%$ RH 0-50°C ± 0.5 °C
Indicator	Have power indicator in the cabinet and operating indicator on core units
Ave Power Consumption	18w
Dual RH Sensor Design	Built-in independent sensors in the drying system and hygrometer provides RH monitoring independent of each other
Brand	Eureka
Country of Manufacture	Taiwan